

3MP Smart 4G Dome ATC Camera



Features

- 3MP (2304 x 1296) Resolution
- All Time Color Vision
- Full Duplex Audio Intercom (Built-in High Sensitivity Mic & Speaker)
- Support 10x Digital Zoom
- Area Motion Detection, Humanoid Detection, Push Raltime Notification on the Application
- Mobile Notification on Human & Motion Detection
- Customized Pre-recorded Voice Alarm
- Support Micro SD Card upto 256GB & Cloud Storage(Optional)
- Compression: H.264 / H.265 / H.265+
- 4G connection.QR code for Easy to add camera in the app
- Monitoring: Mobile/PC Software (TrueCloud)
- Alexa Support

Technical Specification

Product Code	: C3-Q-AP-4G-MY-008
Image Sensor	: 1/2.8" CMOS Sensor
Resolutions	: 3MP (2304 x 1296)
Lens	: 4mm
IR LED	: 4 IR Array
IR Distance	: 20 Meters
White LED	: 4 White Array
White LED Distance	: 15 Meters
Min Illumination	: Color: 0.01 Lux,Black & White: 0.001 Lux
Day & Night	: IR-cut Auto ICR
Light Mode	: Full Color / Infrared / Intelligent
Viewing Angle	: Horizontal: 75°, Vertical: 59°, Diagonal: 88°
Video Streaming	: Main Stream: 2304 x 1296 / 15 fps Sub Stream: 800 x 448 /15 fps
Audio Input/Output	: Two way audio, Built in microphone and speakers
Audio Compression Standard	: AAC/G711A
Zoom	: 10x Digital
DNR	: 3D Digital Noise Reduction
White Balance	: Auto
WDR	: D-WDR
Mirror/Flip	: On / Off
Electronic Shutter	: Auto
Video Tunning	: Contrast, Brightness, Saturation, Sharpness adjustment.
On Screen Display (OSD)	: Date, Time, & Title
AI Features	: Motion Detection, Human Detection.
Privacy Zone	: Support 4 Zone
Monitoring	: Andriod, iOS, Windows (TrueCloud)
Slots	: 4G Sim Card / Micro SD Card
Storage	: Support Micro SD Card upto 256GB & Cloud Storage(Optional)

Protocol	: N1/Onvif/rtmp/rtsp
Connection Mode	: 4G Sim Network / Lan Network
4G Frequency Band	: FDD-LTE: B1/B3/B5/B8; TDD-LTE: B34/B38/B39/B40/B41
Button	: Reset Button
Light Mode Indication	: LED Blink: Not connected to Network, LED Continuous ON: Connected to Network
Connectors	: RJ45 LAN connector (100 Mbps) and DC Power Input
Power Input	: DC: 12V/1A (DC 2.1mm Connector)
Power Consumption	: ≤ 15W
Working Temperature / Humidity	: 0-50° C RH Less than 95% (No Condensation)
Storage Temperature / Humidity	: -20° C to 60° C / 20% to 90% RH
Housing Type	: Plastic
Dimension	: 97mm X108.4mm X 111.3mm (H x W x L)
Net Weight	: 214 Gms
Gross Weight	: 346 Gms

****Note: Product Specifications are subject to change without prior notice.***